PH 28

28 mm SDS-plus 3-mode hammer

Features

- Over sized heavy weight striker delivers 3.4 joules of impact energy
- 4 m cable
- 820 watt motor combined with optimised drilling speed results in unsurpassed drilling performance
- Soft start for precise start of drilling/chiselling
- Low vibration due to ergonomic soft grip on main and side handle
- Soft hammer mode for drilling in sensitive materials
- Greatest durability in class is achieved by utilising integrated metal block technology in the gearing mechanism
- Brush rotation ring (for same power in forward & reverse action)
- Safety clutch protects machine and user if drill bit jams

- X version comes with fast changing FIXTEC adaptor with keyless chuck

RANGE SPEC (1)	PH 28	PH 28 X
Article Number	4933396396	4933396392
Blow energy (EPTA)(J)	3.4	3.4
Full load hammer action (bpm)	0 - 4000	0 - 4000
Full load speed (rpm)	0 - 900	0 - 900
Max. drilling concrete (mm)	28	28
Max. drilling steel (mm)	13	13
Max. drilling wood (mm)	30	30
Power input (W)	820	820
Sound power level (dB(A))	103	103
Sound power level uncertainty (dB(A))	3	3
Sound pressure level (dB(A))	93	93
Sound pressure level uncertainty (dB(A))	3	3
Supplied in	Kitbox	Kitbox
Vibration chiseling (m/s<special id ="27" />)	16	16
Vibration chiselling uncertainty (m/s²)	1.5	1.5
Vibration drilling (m/s<special id="27"/>)	22	22
Vibration drilling into concrete [m|s²]	22	22
Vibration drilling into concrete uncertainty [m|s²]	1.5	1.5
Weight (kg)	2.7	2.9